

# ASPIKLER N



**BUILDINGS &  
CONSTRUCTION**

Drain and sewer cleaning



## APPLICATIONS

For sewer suction.

Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.

## ADVANTAGES

- High resistance to abrasive environment and abrasive transportation media.
- Suitable both for suction and pressure.

## TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: SBR/NR, black, fabric impression.

Temperature range: -30°C to +80°C.





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
100.0 ±1.0	8	116.5 ±1.5	6	15	0.9	450	4.3	20	0095016	1
100.0 ±1.0	8	116.5 ±1.5	6	15	0.9	450	4.3	40	0096724	200
125.0 ±1.2	9.5	144.0 ±1.5	6	15	0.9	550	6.3	20	0094152	1
125.0 ±1.2	9.5	144.0 ±1.5	6	15	0.9	550	6.3	40	5009671	200
150.0 ±1.2	10	170.0 ±1.5	6	15	0.9	650	7.77	20	5008847	1

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

