

CANALKLER 250 S ASSEMBLY



**BUILDINGS &
CONSTRUCTION**

Drain and sewer cleaning



APPLICATIONS

Sewer jetting and heavy duty, high pressure water cleaning.

ADVANTAGES

- | Very low sliding resistance which allows: higher cleaning efficiency, reduction of cleaning time and therefore, reduction of fuel consumption.
- | Longer lifespan thanks to the special cover compound with higher abrasion resistance.
- | Better flexibility, even at low temperatures.
- | Easy to handle and user friendly.
- | Deformation resistance.
- | Extra high strength and security due to aramide reinforcement.

TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: aramide textile, braided.

Cover: SBR/NR, black, smooth. Very low sliding resistance.

Temperature range: -30 °C to +80 °C.

STANDARD/APPROVAL

ZH 1/406 (Guidelines for fluid spray jets).



COUPLINGS/FITTINGS


All hoses are assembled with BSP female/BSP male.

All assembled hoses are pressure tested at 375bar and have an unique hose number.

COMPLEMENTARY INFORMATION

Delivered with test certificate on each factory assembled hose.

Embossed branding



TRELLEBORG

CANALKLER 250 S SEWER CLEANING HOSE WP 250 BAR/3600 PSI quarter/year Made in France



| ID mm | WALL THICKNESS mm | OD mm | WORKING PRESSURE bar | BURSTING PRESSURE bar | BENDING RADIUS mm | WEIGHT kg/m | LENGTH m | ARTICLE NUMBER | STOCK () or min. order m |
|-----------|-------------------------|----------|----------------------------|-----------------------------|-------------------------|----------------|-------------|-------------------|---------------------------------|
| 13.0 ±0.5 | 6.3 ±0.5 | 25.6 | 250 | 625 | 70 | 0.45 | 40 | 5014178 | 1 |
| 13.0 ±0.5 | 6.3 ±0.5 | 25.6 | 250 | 625 | 70 | 0.45 | 60 | 5014179 | 1 |
| 13.0 ±0.5 | 6.3 ±0.5 | 25.6 | 250 | 625 | 70 | 0.45 | 80 | 5014180 | 1 |
| 13.0 ±0.5 | 6.3 ±0.5 | 25.6 | 250 | 625 | 70 | 0.45 | 100 | 5014916 | 1 |
| 13.0 ±0.5 | 6.3 ±0.5 | 25.6 | 250 | 625 | 70 | 0.45 | 120 | 5014005 | 1 |
| 19.0 ±0.6 | 6.3 ±0.5 | 31.6 | 250 | 625 | 90 | 0.61 | 40 | 5014181 | 1 |
| 19.0 ±0.6 | 6.3 ±0.5 | 31.6 | 250 | 625 | 90 | 0.61 | 80 | 5014182 | 1 |
| 19.0 ±0.6 | 6.3 ±0.5 | 31.6 | 250 | 625 | 90 | 0.61 | 100 | 5014459 | 1 |
| 19.0 ±0.6 | 6.3 ±0.5 | 31.6 | 250 | 625 | 90 | 0.61 | 120 | 5014006 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 40 | 5014183 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 50 | 5014874 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 80 | 5014184 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 100 | 5014238 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 120 | 5014007 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 150 | 5014461 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 160 | 5014185 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 180 | 5014186 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 200 | 5014520 | 1 |
| 25.0 ±0.8 | 7.15 ±0.5 | 39.3 | 250 | 625 | 100 | 0.9 | 240 | 5014733 | 1 |
| 32.0 ±1.0 | 7.8 ±0.6 | 47.6 | 250 | 625 | 130 | 1.12 | 40 | 5014187 | 1 |
| 32.0 ±1.0 | 7.8 ±0.6 | 47.6 | 250 | 625 | 130 | 1.12 | 80 | 5014188 | 1 |
| 32.0 ±1.0 | 7.8 ±0.6 | 47.6 | 250 | 625 | 130 | 1.12 | 120 | 5014008 | 1 |
| 32.0 ±1.0 | 7.8 ±0.6 | 47.6 | 250 | 625 | 130 | 1.12 | 150 | 5014466 | 1 |
| 32.0 ±1.0 | 7.8 ±0.6 | 47.6 | 250 | 625 | 130 | 1.12 | 160 | 5014189 | 1 |
| 32.0 ±1.0 | 7.8 ±0.6 | 47.6 | 250 | 625 | 130 | 1.12 | 180 | 5014190 | 1 |
| 32.0 ±1.0 | 7.8 ±0.6 | 47.6 | 250 | 625 | 130 | 1.12 | 200 | 5014655 | 400 |
| 38.0 ±1.0 | 8 ±0.8 | 54.0 | 250 | 500 | 155 | 1.35 | 120 | 5014009 | 1 |

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

